

1.2 MAX
41.2 ± 0.6
28.4
4.2 ± 0.1
4.8
(57.4)
12.6 ± 0.1
4.5 ± 0.1
4.2 ± 0.3
4
20
18
1.9 DIA x 4 WDC
SINTERED STAINLESS ROLLER
BOOT SEAL
3 MAX
TERMINAL SCREW
REFER TO NOTE 4
CONDUIT HOLE
Ø9.7 ± 0.5
KNURLED CAPNUT
Ø4.8
MOUNTING HOLE
OPERATING POSITION
PRETAVEL

- NOTES: 1. SWITCH ENCLOSURE IS OF ZINC ALLOY COATED WITH BLACK FLUOROPLASTICS.
TERMINAL COVER IS PLASTIC.
2. SEAL IS ALREADY ASSEMBLED FOR A CABLE OF 5.8 TO 7.8 DIA.
SEAL IS ATTACHED FOR A CABLE OF 7.5 TO 9.6 DIA.
3. MOUNT COMPLETELY THE TERMINAL COVER AFTER WIRING, TO KEEP THE SEALING
OF TERMINAL HOUSING. TIGHTEN FULLY THE KNUBBED CAPNUT BY HAND WITHOUT
USING A TOOL.
4. TERMINAL COVER AND TERMINAL SCREWS ARE FURNISHED UNASSEMBLED.